




## Airhandler LV50

Compact mobile ventilation unit that can be suspended, with a heating capacity of 50 kW and a cooling capacity of 25 kW. The energy-efficient unit is easy to connect to an air hose or a duct system. The temperature can be controlled remotely or using the integrated thermostat. Can be used to control the temperature in small to medium-sized rooms or to prevent frost in large buildings.

### Standard accessories LV50



Water connection

Electrical power connection (A)

### Optional accessories LV50



Extension power cables

Water hoses

Airhoses

### Technical specifications LV50

Cooling capacity <sup>1</sup>	25 kW
Heating capacity <sup>2</sup>	50 kW
Current (nominal)	3.3 A
Capacity steps	2 or Frequency controlled
Max. air flow	4000 m <sup>3</sup> /h
Power connection	SCHUKO 230V
Voltage	230 V
Recommended Fuses	6 A
Phases	1 + N + E
Water connection	GEKA 1?
Air duct(s)	300 mm
Length	915 mm
Width	600 mm
Height	1250 mm
Weight	130 kg
Sound level (at 10 m)	53 dB(A)

<sup>1</sup> Cooling: Water 6 - 12 °C, air 28 °C / 60% RV

<sup>2</sup> Heating: Water 70 - 50 °C, air 10 °C / 80% RV